

SISTEMA ACUSTICOMAGNETICO MODELLO "MONOANTENNA"



MTC PROMAX AM

M.T.C. PROMAX AM System operates at 58 kHz.

Features:

- Suitable to apply full dressed advertising panels
- Visual (RGB) and audible alarm
- Optional People Counting
- Optional Metal - and Magnet detection
- Near Tag Alarm
- Life line (RGB led will blink every 3 seconds)
- Optional remote service and diagnostics
- Optional remote data collection and analytics
- Low energy-environment friendly

Standard delivered with black inlays.



DATE GROUP S.r.l. - Sistemi integrati di sicurezza e antitaccheggio

Sede commerciale, amministrativa e magazzini: Strada San Mauro 79/4 - 10156 TORINO -

Telefono 011/2239007 Fax 011/2239007 PARTITA IVA 07850030011

capitale sociale €.100.000,00 (interamente versato)

e-mail: info@dategroup.it - www.dategroup.it - www.dategroup-antitaccheggio.com.

Specifications	<i>Mono System</i>
Description	MTC PROMAX Mono System
Article number	XS-A2MPROM58TRX
Dimensions	1530 x 310 x 45 mm
Frequency	AM, 58 kHz
Operating temperature	Up to 85°C / 185°F
Power supply	110/220 volt
Detection range DR-Labels	Up to 0.9 m both sides
Detection range hard tags (X50, MTC Dome, Mini pencil)	Up to 1.20 m both sides
Detection range when using Xtreme Tag	Up to 1.40 m both sides

Specifications	<i>Dual System</i>
Description	MTC PROMAX Dual System
Article number	XS-A2MPROM58C
Dimensions	1530 x 310 x 45 mm
Frequency	AM, 58 kHz
Operating temperature	Up to 85°C / 185°F
Power supply	110/220 volt
Detection range DR-Labels	Up to 1.80 m
Detection range hard tags (X50, MTC Dome, Mini pencil)	Up to 2.40 m
Detection range when using Xtreme Tag	Up to 2.80 m

